



| TECHNICAL DATA | | STANDARD | | | |
|--|--|--|-----------|-----------|-----------|
| EXTERNAL DIMENSIONS | | | | | |
| width | | 450 mm | | | |
| depth | | 535 mm | | | |
| height | | 700 mm | | | |
| WEIGHT | | | | | |
| | | 37 kg | | | |
| VOLTAGE | | | | | |
| | | 230V 50Hz | | | |
| POWER REQUIRED | | | | | |
| | | 3200 W | | | |
| WATER HARDNESS | | | | | |
| | | 2-8 °F | | | |
| INLET WATER PRESSURE | | | | | |
| | | 200-400 kPa | | | |
| CROCKERY DIMENSIONS | | | | | |
| plates diameter | | 295 mm | | | |
| glasses max. height | | 305 mm | | | |
| RACK DIMENSIONS | | | | | |
| | | 400X400 mm | | | |
| RACK EQUIPMENT | | | | | |
| | | 2XC121 - 1X10728 - 1X15060 | | | |
| WASHING CYCLES (s) | | | | | |
| | | 1<60> | 2<90> | 3<120> | 4<180> |
| WATER SUPPLY 55°C | | | | | |
| racks/h(*) ⁽¹⁾ | | 60 | 40 | 30 | 20 |
| WATER SUPPLY 10°C | | | | | |
| racks/h(*) ⁽¹⁾ | | 16 | 16 | 16 | 16 |
| WATER CONSUMPTION / CYCLE (water pressure 200kPa) | | | | | |
| | | 1.8 L | | | |
| BOILER CAPACITY | | | | | |
| | | 3.4 L | | | |
| BOILER HEATING ELEMENT | | | | | |
| | | 2800 W | | | |
| RINSING TEMPERATURE (SET) | | | | | |
| | | 85°C | | | |
| TANK CAPACITY | | | | | |
| | | 14.5 L | | | |
| TANK HEATING ELEMENT | | | | | |
| | | 1250 W | | | |
| TANK TEMPERATURE (SET) | | | | | |
| | | 55°C | | | |
| PUMP POWER | | | | | |
| | | 400 W (185 L/min) | | | |
| DRAIN PUMP (optional) | | | | | |
| | | 25 W h MAX vidange 0.8m (40 L/min ^{***}) | | | |
| NOISE | | | | | |
| | | 60.6[CF] 61.2[LS] (dB(A)±0.7) | | | |

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.