



	WATER CONNECTION 3/4" GAS
	DRAINING PIPE Ø 28mm
	ELECTRICAL SUPPLY

(***) MIN 130-MAX 200 mm

TECHNICAL DATA						
EXTERNAL DIMENSIONS						
width		720 mm				
depth		735 mm				
height		1445/1915(open hood) mm				
WEIGHT(basic version)		104 kg				
VOLTAGE		400V 3N 50Hz				
POWER REQUIRED		10490 W				
WATER HARDNESS		2-8 °F				
INLET WATER PRESSURE		200-400 kPa				
CROCKERY DIMENSIONS						
plates diameter		410 mm				
trays max. dimension		600X400 mm				
RACK DIMENSION		500X500+SPECIAL STEEL RACK 500X600 mm				
RACK EQUIPMENT		1XC44 - 1XC86/A - 1X11600054				
WASHING CYCLES	(s)	1 (50)	2 (90)	3 (120)	4 (180)	----
WATER SUPPLY 55°C						
racks/h(*) ⁽¹⁾		72	40	30	20	--
WATER SUPPLY 10°C						
racks/h(*) ⁽¹⁾		35	35	30	20	--
WATER CONSUMPTION / CYCLE		2.6 l				
BOILER CAPACITY		15 l				
BOILER HEATING ELEMENT		9000 W				
RINSING TEMPERATURE (SET)		85°C				
TANK CAPACITY		42 l				
TANK HEATING ELEMENT		2700 W				
TANK TEMPERATURE (SET)		55°C				
PUMPS POWER washing		1490 W (800 l/min ^{***})				
DRAIN PUMP (optional)		25 W (40 l/min ^{***})				
NOISE		66,4±0.7 dB(A)				

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.