



TECHNICAL DATA					
<b>EXTERNAL DIMENSIONS</b>					
width	650 mm				
depth	750 mm				
height	1690/2060 (open door) mm				
WEIGHT(basic version)	110 kg				
VOLTAGE	400V 3N 50Hz				
POWER REQUIRED	8000 W				
WATER HARDNESS	2-8 °F				
INLET WATER PRESSURE	200-400 kPa				
<b>CROCKERY DIMENSIONS</b>					
plates diameter	---				
basket max. height	805 mm				
RACK DIMENSIONS	550X665 mm				
RACK EQUIPMENT	1XC86/A - 1XC87/B - 1XC97/A - 1XC100				
WASHING CYCLES (min)	1 (2)	2 (4)	3 (6)	4 (8)	----
<b>WATER SUPPLY 55°C</b>					
racks/h(*) <sup>(1)</sup>	30	15	10	7.5	----
<b>WATER SUPPLY 10°C</b>					
racks/h(*) <sup>(1)</sup>	13	13	10	7.5	----
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	4,7 L				
BOILER CAPACITY	10 L				
BOILER HEATING ELEMENT	6000 W				
RINSING TEMPERATURE (SET)	85°C				
TANK CAPACITY	35 L				
TANK HEATING ELEMENT	2700 W				
TANK TEMPERATURE (SET)	55°C				
RINSING PUMP	150 W ( 14 L /min )				
PUMP POWER	2000 W (810 L/min <sup>***</sup> )				
DRAIN PUMP (optional)	190 W (120 L/min <sup>***</sup> )				
ACOUSTIC PRESSURE	63.8 dB(A)				

(\*) STANDARD TERMOSTOP

(\*\*\*) MAXIMUM FLOW RATE

<sup>(1)</sup> In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.